

POLYCHLORINATED BIPHENYLS (PCB) WASTE DATA SHEET
Schedule "A" Attachment

Rollins Environmental Services Inc.

P. O. Box 609, Deer Park, Texas 77536 (713) 479-6001

BILLING INFORMATION:

COMPANY BRASS WORKS
NAME ALASKAN ~~COPPER~~ BRASS CO.
ADDRESS 628 SOUTH HANFORD
CITY SEATTLE
STATE WASHINGTON ZIP 98124
CONTACT JAMES C. BROWN Phone 206-623-5800

MANIFEST INFORMATION:

(For proper return of Shipping Control)
(Ticket, please complete the following)

COMPANY
NAME SAME
ADDRESS
CITY
STATE ZIP
CONTACT
PHONE

RES HO#-

To be assigned by RES

PICK-UP LOCATION:

COMPANY
NAME SAME
ADDRESS
CITY
STATE ZIP
USEPA ID NO. NOT PROVIDED PCB
TEXAS TDWR ID NO.
CONTACT
PHONE

LIQUID PCB WASTE DESCRIPTION:

Name of Original PCB Fluid INERTEEN Quantity 30 GAL
Name of Flushing Solvent Used DIESEL OIL Quantity 40 GAL
Total Volume of Disposal 70.80 Gallons Spec. Gravity 8.5 lbs.
PCB Concentration 500 P.P.M. How was concentration determined? NAME PLATE
The waste for disposal is a liquid with sludge? YES NO X
The waste contains water? YES NO X NOW MUCH

LABORATORY DATA ON WASTE:

Heat of Combustion BTU/LB Ash Wt %
Flash Point °F Viscosity Centipoise
(If under 140°F it is a D001 Hazardous Waste.)
Vapor Pressure psi

METALS: NONE

This Section must be completed with "0" or actual content.

*Pb Mg/l Other Mg/l *S % Wt
*Hg Mg/l Other Mg/l *Cl % Wt

*NOTE: Metals analyses are required, please complete these blanks.

STORAGE: Currently stored in:

Transformer X-RAY POWER UNIT
1k

WILL BE IN

55 Gallon Drums X
Other (Describe)

SOLID PCB WASTE DESCRIPTION:

Capacitors In drums with:	DOT Spec. Type of Drum	Quantity	Total Wt. Pounds
Leaking Capacitors:			
Non-Leaking Capacitors:	<u>17-C OPEN</u>	<u>1002</u>	<u>300 lbs EST</u>

Capacitors in Boxes:	Type of Box Steel, Wood, etc.	Quantity	Total Wt. Pounds

Capacitors on Pallets:	No. of Pallets	Total Quantity of Capacitors	Total Wt. Pounds

Other PCB Articles: (Please Describe) TYVER, GLOVES, RESPIRATOR CARTRIDGE
PACKED WITH CAPACITORS

TRANSPORTATION REQUIREMENTS:

Liquid PCB Bulk Shipments
Access for 40-foot tractor
and tanker.

Access to within 20-feet of
load point.

Truck will be equipped with
one each:

2"x20' Loading Line

2"x20' Venting Hose

Client must have 2 inch vent
line connection within 20
feet of the load point.

Client must provide for
pumping material into
the tanker.

Liquid PCB Drum Shipments

Access for 40-foot tractor
and van.

Access to within 14-feet of
vertical clearance.

All drums will be inspected
by driver before loading.

Driver has authority to
reject a drum he deems
unsafe for transport.

Client will load drums under
driver supervision.

DOT approved PCB drum
(Stamped on drum): Rollins'
HO-XXXX Number should be
marked on the top and side
of the drum.

Solid PCB Shipments

Access for 40-foot tractor
and van.

Access to within 14-feet of
vertical clearance.

All materials will be
inspected by driver
before loading.

Driver has authority to
reject materials he deems
unsafe for transport.

Client will load the
materials under driver
supervision.

If in drum(s): Rollins'
HO-XXXX Number should
be marked on the top and
side of the drum.

SCHEDULING:

Should you have any questions regarding this form, please call (713) 479-6001.

NAME (Print) WILLIAM H. FINNEY

Title PRESIDENT

* Signature William H. Finney

Date TECREP, INC.

IMPORTANT: ALL WASTE DATA SHEETS MUST BE SIGNED AND DATED.

* BILLING TO TECREP INC

2212 SOUTH WEST TEMPLE
SUITE 46
SALT LAKE CITY, UTAH
84115